



SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: EZ-6010A

Product type: DUCT SEALANT

Restriction of use: None identified

Company Address: Precision Adhesives
131 Brown Street
Yatesville, Pittston, PA 18640

Telephone numbers: 570-654-6735

Transport Emergency phone: Chemtrec 800-424-9300

Medical Emergency phone: Poison Control Center 1.877.671.4608

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Target Organ Systemic Toxicity (single exposure), Category 3

Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapour

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Pictograms:



Precautionary statements

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

- P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical, lighting, ventilating equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P261 - Avoid breathing mist, spray, vapours
 P264 - Wash exposed skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear eye protection, face protection, protective clothing, protective gloves
 P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P312 - Call a POISON CENTER/doctor/.../if you feel unwell
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) for extinction
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed

Hazards not otherwise classified

EUH 066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

| Components | CAS# | % |
|--------------|---------|----------|
| ACETONE* | 67-64-1 | 45 to 47 |
| elastomer | | 18 to 25 |
| resins | | 10 to 15 |
| inert filler | | 15 to 25 |

SECTION 4: FIRST-AID MEASURES

SIGNS AND SYMPTOMS OF EXPOSURE:

Eyes: Irritation

Skin: Irritation

Inhalation: dizziness, drowsiness, nausea

FIRST AID & EMERGENCY PROCEDURES:

Eyes: Immediately flush with plenty of water for at least 15 minutes, lifting eyelids occasionally during flushing to facilitate irrigation. Seek medical attention.

Skin: Immediately wash skin with soap and water. Remove contaminated clothing. Seek medical attention if irritation persists.

Inhalation: Remove to fresh air. If breathing is difficult, seek medical attention.

Ingestion: Take immediately to hospital or physician.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: USE WATER, DRY CHEMICALS OR CO₂

FLASH POINT: 0° F.T.C.C

| | | |
|-------------------|---------|----------|
| FLAMMABLE LIMITS: | LEL | UEL |
| ACETONE | 2.5 VOL | 12.8 VOL |

UNUSUAL FIRE & EXPLOSION HAZARDS: Vapors concentrated in a confined or poorly ventilated area can be ignited upon contact with a spark, flame or high intensity source of heat. This can occur at concentrations between 12% and 19% by volume.

Extinguishing Media: Dry Chemical, Carbon Dioxide, Foam, Water Spray.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and full protective clothing. Water may be used to cool fire-exposed containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Soak up with absorbent material, remove to a chemical disposal area. Enclose with diking material to prevent seepage into any natural bodies of water. Absorb residue and dispose of all waste according to all local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep container closed when not in use. Do not breath gas/fumes/vapor/spray. Wash thoroughly after handling. Do not store above 100° F.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

| Hazardous Component | C.A.S. # | ACGIH TWA/ppm | ACGIH STEL/ppm | OSHA TWA/ppm | Sara Title III |
|----------------------------|-----------------|----------------------|-----------------------|---------------------|-----------------------|
| Acetone | 67-64-1 | 750 | 1000 | 1000 | Yes |

Respiratory Protection: The use of respiratory protection depends on vapor concentration above the time-weighted TLV. Use a respirator/gas mask with appropriate cartridges and canister (NIOSH approved) or supplied air equipment, depending on airborne concentration.

Ventilation: General mechanical ventilation may be sufficient to keep product vapor concentrations within specified time-weighted TLV ranges. If general ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required if vapor concentrations cannot be reduced to below the TLV by ventilation.

Protective Gloves: The use of gloves which are impermeable to the specific material handled is advised to prevent skin irritation and absorption.

Other Protective Clothing or Equipment: Safety glasses, chemical goggles and/or face shield are recommended to safeguard against potential eye contact, irritation or injury.

Special clothing is advised as good chemical handling practice. The availability of eye wash and safety showers in work areas is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|---------------------------------------|---------------------------------------|------------------------------------|------|
| Boiling Point | 55 °F | Vapor Density (AIR=1) | 2.0 |
| Specific Gravity (H ₂ O=1) | 1.01 | Evaporation Rate (Butyl Acetate=1) | 14.4 |
| Vapor Pressure (mm Hg) | 181 | Solubility in Water | NIL |
| Percent Volatile by Weight | 49 % | | |
| Appearance and Odor | Aluminum colored, mastic, ketone odor | | |

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable **HAZARDOUS POLYMERIZATION:** May not occur

CONDITIONS TO AVOID: Exposure to heat, sparks, open flames, static electricity.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS OR BYPRODUCTS: Carbon monoxide, carbon dioxide, smoke, fumes, other unidentified toxic materials.

SECTION 11: TOXICOLOGICAL INFORMATION

| Hazardous Component | C.A.S. # | ACGIH TWA/ppm | ACGIH STEL/ppm | OSHA TWA/ppm | Sara Title III |
|----------------------------|-----------------|----------------------|-----------------------|---------------------|-----------------------|
| Acetone | 67-64-1 | 750 | 1000 | 1000 | Yes |

Signs And Symptoms Of Exposure:

Eyes: Irritation Skin: Irritation Inhalation: dizziness, drowsiness, nausea

Potential Acute Health Effects:

Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC.

MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available.

The substance may be toxic to blood, kidneys, the nervous system, liver, brain, central nervous system (CNS).

Repeated or prolonged exposure to the substance can produce target organs damage.

SECTION 12: ECOLOGICAL INFORMATION

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of only in accordance with local, state, and federal rules and regulations.

SECTION 14: TRANSPORT INFORMATION

D.O.T. Shipping Name: UN1133, Adhesives, 3, PG II

HMIS Rating: Health: 1

Flammability: 3

Reactivity: 0

Contains:

| | |
|---------|------------|
| | cas number |
| Acetone | 67-64-1 |

D.O.T. Label: Flammable liquid

The DOT Hazardous Materials Regulations (HMR) include exceptions for certain shipments. For example, the HMR includes a “limited quantity” exception based on a reference to [49 CFR 173.150 through 173.155 and 173.306](#) from Column 8A of the Hazardous Materials Table at [49 CFR 172.101](#). This exception may apply to shipments of this product packaged entirely in 0.1 pound caulking tubes.

SECTION 15: REGULATORY INFORMATION

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Benzene

California prop. 65 (no significant risk level): Benzene: 7 mg/day (value) California prop. 65 (acceptable daily intake level): Benzene: 7 mg/day (value)

California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene

Connecticut hazardous material survey.: acetone

Illinois toxic substances disclosure to employee act: acetone

Illinois chemical safety act: Toluene, hexane, acetone

New York release reporting list: acetone

Rhode Island RTK hazardous substances: acetone

Pennsylvania RTK: acetone

Florida: acetone

Minnesota: acetone

Michigan critical material: acetone

Massachusetts RTK: acetone

Massachusetts spill list: acetone

New Jersey: acetone

New Jersey spill list: acetone

Louisiana spill reporting: acetone

California Director's List of Hazardous Substances.: acetone

TSCA 8(b) inventory: acetone

TSCA 8(d) H and S data reporting: acetone: Effective date: 10/04/82; Sunset Date: 10/4/92

SARA 313 toxic chemical notification and release reporting: acetone

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada):

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).

CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC): R11- Highly flammable. R20- Harmful by inhalation. S16- Keep away from sources of ignition - No smoking. S25- Avoid contact with eyes. S29- Do not empty into drains. S33- Take precautionary measures against static discharges.

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 3

Reactivity: 0

Personal Protection: h

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 3

Reactivity: 0

Specific hazard: none

SECTION 16: OTHER INFORMATION

Updated: 10/1/15

SPECIAL COMMENT REGARDING ALL MATERIALS MANUFACTURED

All information, recommendations and suggestions appearing herein concerning our products are based upon test data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity and suitability for use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Precision Adhesives as to the effects or such use, the results to be obtained, or the safety and toxicity of the product nor does Precision Adhesives assume any liability arising out of use, by others, of the product referred to herein. The information herein is not to be considered as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.